

## XR720C

## Digital controller for normal temperature with "off cycle" defrost

C: 32x74mm, panel mounting

### Features

<b>First display</b>	3 digits, d.p., -
<b>Second display</b>	4 digits, d.p., -
<b>Keyboard</b>	4 push buttons
<b>Power supply</b>	110, 230Vac

### Probe inputs

<b>Thermostat</b>	NTC
<b>Display</b>	NTC

### Digital inputs

<b>Alarm, door switch, light, defrost</b>	configurable
---	--------------

### Relay outputs

<b>Compressor</b>	8A
-------------------	----

### Other Outputs

<b>Hot Key/Prog Tool Kit output</b>	present
<b>Infrared output</b>	optional

### Other

<b>Buzzer</b>	present
<b>Real time clock</b>	present

### Measurement

<b>Measurement range</b>	probe dependent
<b>Accuracy</b>	Better than 1% of full scale

### Generals

<b>Housing</b>	Self extinguishing ABS
<b>Front protection</b>	IP65 with gasket
<b>Display type</b>	1st: red LED (8.0mm high) 2nd: yellow LED (5.6mm high)
<b>Data Storage</b>	EEPROM memory
<b>Operating temperature</b>	0°÷60°C



	32°÷140°F
<b>Storage temperature</b>	-30°÷85°C 22°÷185°F
<b>Relative humidity</b>	20÷85%
<b>Resolution</b>	0.1°C or 1°F
<b>Connection</b>	Screw-terminal block <2.5mm <sup>2</sup>