

## XR30D

## Digital controller for N.T. with off cycle defrost and additional configurable r

D: 4 DIN Rail mounting

### Features

<b>Display</b>	3 digits, d.p., -
<b>Power supply</b>	24, 110, 230Vac

### Probe inputs

<b>Thermostat</b>	NTC / PTC
-------------------	-----------

### Digital inputs

<b>Alarm, AUX, start defrost, door switch, pressure switch</b>	configurable
--	--------------

### Relay outputs

<b>Compressor</b>	no 8A / nc 5A, 20A optional
<b>Alarm or auxiliary</b>	no 8A / nc 5A

### Other Outputs

<b>Hot Key output</b>	present
-----------------------	---------

### Other

<b>Functions</b>	HACCP
<b>Buzzer</b>	optional

### Measurement

<b>Measurement range</b>	probe dependent
<b>Accuracy</b>	Better than 1% of full scale

### Generals

<b>Housing</b>	Self extinguishing ABS
<b>Display type</b>	red LED (13.2mm high)
<b>Data Storage</b>	EEPROM memory
<b>Operating temperature</b>	0°÷60°C 32°÷140°F
<b>Storage temperature</b>	-30°÷85°C 22°÷185°F
<b>Relative humidity</b>	20÷85%
<b>Resolution</b>	0.1°C or 1°F



Connection	Screw-terminal block <2.5mm <sup>2</sup>
------------	---

---