

## XW35VS

## Digital controller for N. T. applications with "off cycle" defrost and light and

V: 100x64mm, panel mounting

### Features

<b>Display</b>	3 digits, d.p., -
<b>Keyboard</b>	6 push buttons
<b>Power supply</b>	24, 110, 230Vac

### Probe inputs

<b>Thermostat</b>	NTC / PTC
<b>Display</b>	NTC / PTC

### Digital inputs

<b>Alarm, start defrost, door switch, pressure switch</b>	configurable
---	--------------

### Relay outputs

<b>Compressor</b>	16A
<b>Fans</b>	8A
<b>Light, ON/OFF</b>	16A

### Other Outputs

<b>Hot Key/Prog Tool Kit output</b>	present
-------------------------------------	---------

### Other

<b>Buzzer</b>	optional
---------------	----------

### Measurement

<b>Measurement range</b>	probe dependent
<b>Accuracy</b>	Better than 1% of full scale

### Generals

<b>Housing</b>	Self extinguishing ABS
<b>Front protection</b>	IP65 with gasket
<b>Display type</b>	red LED (13.2mm high)
<b>Data Storage</b>	EEPROM memory
<b>Operating temperature</b>	0°÷60°C 32°÷140°F
<b>Storage temperature</b>	-30°÷85°C



	22°÷185°F
<b>Relative humidity</b>	20÷85%
<b>Resolution</b>	0.1°C or 1°F
<b>Connection</b>	2.8mm and 6.3mm faston